[details="Simple system report"]
```
app version: 27.1-r0
current_network:
  ip: 192.168.42.1
  security: wpa-psk
  ssid: reach-base:D2:FA
enabled: true
mode: hotspot
base_mode:
  base_coordinates:
    antenna_offset: 2.877
    coordinates:
      height: 32.371
      latitude: 45.5296278625
      longitude: -73.1511783675
    format: LLH
    mode: manual
  output:
    io_type: lora
    settings:
      cloud:
        mount_point: ''
      lora:
        air_rate: 9.11
        frequency: 910000
        output_power: 20
      ntripsvr:
        address: ''
        mount_point: ''
        password: '***'
        port: -1
      serial:
        baud_rate: 38400
        device: ttyEXTS0
      tcpcli:
        address: localhost
        port: 9001
      tcpsvr:
        port: 9000
  rtcm3_messages:
    message_1004:
      enabled: false
      frequency: 1
    message_1006:
      enabled: true
      frequency: 0.1
    message_1008:
      enabled: false
      frequency: 0.1
```

```
    message_1012:
      enabled: false
      frequency: 1
    message_1033:
      enabled: false
      frequency: 0.1
    message_1074:
      enabled: true
      frequency: 0.5
    message_1084:
      enabled: true
      frequency: 0.5
    message_1094:
      enabled: true
      frequency: 0.5
    message_1124:
      enabled: true
      frequency: 0.5
    message_1230:
      enabled: true
      frequency: 0.1
bluetooth:
  enabled: false
  pairing:
    discoverable: false
    pin: '***'
correction_input:
  base_corrections:
    io_type: 'off'
    settings:
      bluetooth:
        send_position_to_base: false
      cloud:
        mount_point: ''
        send_position_to_base: true
      lora:
        air_rate: 9.11
        frequency: 910000
        output_power: 20
        send_position_to_base: false
      ntripcli:
        address: ''
        mount_point: ''
        password: '***'
        port: -1
        send_position_to_base: true
        username: ''
      serial:
        baud_rate: 38400
        device: ttyEXTS0
```

```
        send_position_to_base: false
      tcpcli:
        address: localhost
        port: 10001
        send_position_to_base: true
      tcpsvr:
        port: 10000
        send_position_to_base: true
device:
  power_on_bottom_connector: false
  privacy_policy_accepted: true
  role: null
  rv3_banner_shown: false
  usage_analysis_accepted: false
logging:
  logs:
    base:
      autostart: false
      format: RTCM3
      started: true
    correction:
      autostart: false
      format: RTCM3
      started: true
    raw:
      autostart: false
      format: UBX
      rinex_options:
        logging_interval: 1
        marker_name: null
        pole_height: null
        satellite_systems:
          beidou: false
          galileo: false
          glonass: false
          gps: true
          qzss: false
          sbas: false
        time_adjustments_enabled: false
      started: true
    solution:
      autostart: false
      format: LLH
      started: true
  settings:
    debug: false
    interval: 24
    overwrite: true
network:
  tcp_over_modem: false
```

```
position_output:
  output1:
    io_type: bluetooth
    nmea_settings:
      bluetooth:
        gga:
          enabled: true
          update_rate: 1
        gsa:
          enabled: true
          update_rate: 1
        gst:
          enabled: true
          update_rate: 1
        gsv:
          enabled: true
          update_rate: 1
        main_talker_id: gn
        rmc:
          enabled: true
          update_rate: 1
        vtg:
          enabled: true
          update_rate: 1
        zda:
          enabled: true
          update_rate: 1
      serial:
        gga:
          enabled: true
          update_rate: 1
        gsa:
          enabled: true
          update_rate: 1
        gst:
          enabled: true
          update_rate: 1
        gsv:
          enabled: true
          update_rate: 1
        main_talker_id: gn
        rmc:
          enabled: true
          update_rate: 1
        vtg:
          enabled: true
          update_rate: 1
        zda:
          enabled: true
          update_rate: 1
```

```
  tcpcli:
    gga:
      enabled: true
      update_rate: 1
    gsa:
      enabled: true
      update_rate: 1
    gst:
      enabled: true
      update_rate: 1
    gsv:
      enabled: true
      update_rate: 1
    main_talker_id: gn
    rmc:
      enabled: true
      update_rate: 1
    vtg:
      enabled: true
      update_rate: 1
    zda:
      enabled: true
      update_rate: 1
  tcpsvr:
    gga:
      enabled: true
      update_rate: 1
    gsa:
      enabled: true
      update_rate: 1
    gst:
      enabled: true
      update_rate: 1
    gsv:
      enabled: true
      update_rate: 1
    main_talker_id: gn
    rmc:
      enabled: true
      update_rate: 1
    vtg:
      enabled: true
      update_rate: 1
    zda:
      enabled: true
      update_rate: 1
settings:
  bluetooth:
    format: NMEA
  serial:
```

```
      baud_rate: 38400
      device: ttyEXTS0
      format: ERB
    tcpcli:
      address: localhost
      format: ERB
      port: 9000
    tcpsvr:
      format: LLH
      port: 9001
output2:
  io_type: tcpsvr
  nmea_settings:
    bluetooth:
      gga:
        enabled: true
        update_rate: 1
      gsa:
        enabled: true
        update_rate: 1
      gst:
        enabled: true
        update_rate: 1
      gsv:
        enabled: true
        update_rate: 1
      main_talker_id: gn
      rmc:
        enabled: true
        update_rate: 1
      vtg:
        enabled: true
        update_rate: 1
      zda:
        enabled: true
        update_rate: 1
    serial:
      gga:
        enabled: true
        update_rate: 1
      gsa:
        enabled: true
        update_rate: 1
      gst:
        enabled: true
        update_rate: 1
      gsv:
        enabled: true
        update_rate: 1
      main_talker_id: gn
```

```
    rmc:
      enabled: true
      update_rate: 1
    vtg:
      enabled: true
      update_rate: 1
    zda:
      enabled: true
      update_rate: 1
  tcpcli:
    gga:
      enabled: true
      update_rate: 1
    gsa:
      enabled: true
      update_rate: 1
    gst:
      enabled: true
      update_rate: 1
    gsv:
      enabled: true
      update_rate: 1
    main_talker_id: gn
    rmc:
      enabled: true
      update_rate: 1
    vtg:
      enabled: true
      update_rate: 1
    zda:
      enabled: true
      update_rate: 1
  tcpsvr:
    gga:
      enabled: true
      update_rate: 1
    gsa:
      enabled: true
      update_rate: 1
    gst:
      enabled: true
      update_rate: 1
    gsv:
      enabled: true
      update_rate: 1
    main_talker_id: gn
    rmc:
      enabled: true
      update_rate: 1
    vtg:
```

```
          enabled: true
          update_rate: 1
        zda:
          enabled: true
          update_rate: 1
    settings:
      bluetooth:
        format: NMEA
      serial:
        baud_rate: 38400
        device: ttyEXTS0
        format: ERB
      tcpcli:
        address: localhost
        format: ERB
        port: 9000
      tcpsvr:
        format: LLH
        port: 9001
positioning_settings:
  elevation_mask_angle: 15
  glonass_ar_mode: false
  gnss_settings:
    positioning_systems:
      beidou: false
      galileo: false
      glonass: true
      gps: true
      qzss: false
    update_rate: 1
  gps_ar_mode: fix-and-hold
  max_horizontal_acceleration: 1
  max_vertical_acceleration: 1
  positioning_mode: static
  snr_mask: 35
sound:
  mute: false
  volume: 100
```
[/details]