

[details="Simple system report"]

...

app version: 30.2-r0
current_network:
 ip: 192.168.1.90
 security: wpa-psk
 ssid: AIRSEED 5G
enabled: true
mode: client
base_mode:
 base_coordinates:
 accumulation: 120
 antenna_offset: 1.865
 coordinates:
 height: 179.53
 latitude: -33.4755163
 longitude: 150.9683112
 mode: fix-and-hold
output:
 io_type: lora
 settings:
 lora:
 air_rate: 9.11
 frequency: 918100
 output_power: 20
 ntripcaster:
 mount_point: REACH
 password: '****'
 port: 2101
 username: reach
 ntripsvr:
 address: ntrip.data.gnss.ga.gov.au
 mount_point: MGRV00AUS0
 password: '****'
 port: 2101
 serial:
 baud_rate: 38400
 device: ttyEXTS0
 tcpcli:
 address: localhost
 port: 9001
 tcpsvr:
 port: 9000
rtcm3_messages:
 message_1002:
 enabled: true
 frequency: 1
 message_1006:
 enabled: true
 frequency: 0.1

message_1010:
 enabled: true
 frequency: 0.5
message_1097:
 enabled: true
 frequency: 0.5
message_1107:
 enabled: true
 frequency: 0.5
message_1117:
 enabled: true
 frequency: 1
message_1127:
 enabled: true
 frequency: 0.5
bluetooth:
 enabled: true
 pairing:
 discoverable: false
 no_input_no_output: true
 pin: '****'
correction_input:
 base_corrections:
 io_type: ntripcli
 settings:
 bluetooth:
 send_position_to_base: false
 lora:
 air_rate: 9.11
 frequency: 918100
 output_power: 20
 send_position_to_base: false
 ntripcli:
 address: ntrip.data.gnss.ga.gov.au
 mount_point: MGRV00AUS0
 password: '****'
 port: 443
 send_position_to_base: true
 username: mfisher
 serial:
 baud_rate: 38400
 device: ttyEXTS0
 send_position_to_base: false
 tcpcli:
 address: localhost
 port: 10001
 send_position_to_base: true
 tcpsvr:
 port: 10000
 send_position_to_base: true

device:
power_on_bottom_connector: false
privacy_policy_accepted: true
role: null
rv3_banner_shown: false
usage_analysis_accepted: false
logging:
logs:
 autostart: true
 base:
 enabled: true
 format: RTCM3
 raw:
 enabled: true
 format: RINEX
 rinex_options:
 logging_interval: 0
 marker_name: null
 pole_height: null
 preset: default
 satellite_systems:
 beidou: true
 galileo: true
 glonass: true
 gps: true
 qzss: true
 sbas: false
 time_adjustments_enabled: false
 version: '3.03'
 solution:
 enabled: true
 format: LLH
 started: true
 settings:
 interval: 24
 overwrite: true
 simultaneous_logging: false
position_output:
output1:
 io_type: bluetooth
 nmea_settings:
 bluetooth:
 ebp:
 enabled: true
 update_rate: 1
 gga:
 enabled: true
 update_rate: 1
 gsa:
 enabled: true

update_rate: 1
gst:
 enabled: true
 update_rate: 1
gsv:
 enabled: true
 update_rate: 1
main_talker_id: gn
rmc:
 enabled: true
 update_rate: 1
vtg:
 enabled: true
 update_rate: 1
zda:
 enabled: true
 update_rate: 1
serial:
 ebp:
 enabled: true
 update_rate: 1
 gga:
 enabled: true
 update_rate: 1
 gsa:
 enabled: true
 update_rate: 1
 gst:
 enabled: true
 update_rate: 1
 gsv:
 enabled: true
 update_rate: 1
 main_talker_id: gn
 rmc:
 enabled: true
 update_rate: 1
 vtg:
 enabled: true
 update_rate: 1
 zda:
 enabled: true
 update_rate: 1
tcpcli:
 ebp:
 enabled: true
 update_rate: 1
 gga:
 enabled: true
 update_rate: 1

gsa:
 enabled: true
 update_rate: 1
gst:
 enabled: true
 update_rate: 1
gsv:
 enabled: true
 update_rate: 1
main_talker_id: gn
rmc:
 enabled: true
 update_rate: 1
vtg:
 enabled: true
 update_rate: 1
zda:
 enabled: true
 update_rate: 1
tcpsvr:
 ebp:
 enabled: true
 update_rate: 1
 gga:
 enabled: true
 update_rate: 1
 gsa:
 enabled: true
 update_rate: 1
 gst:
 enabled: true
 update_rate: 1
 gsv:
 enabled: true
 update_rate: 1
 main_talker_id: gn
 rmc:
 enabled: true
 update_rate: 1
 vtg:
 enabled: true
 update_rate: 1
 zda:
 enabled: true
 update_rate: 1
settings:
 bluetooth:
 format: NMEA
 serial:
 baud_rate: 38400

device: ttyEXTS0
format: ERB
tcpcli:
address: localhost
format: ERB
port: 9000
tcpsvr:
format: LLH
port: 9001
output2:
io_type: tcpsvr
nmea_settings:
bluetooth:
ebp:
enabled: true
update_rate: 1
gga:
enabled: true
update_rate: 1
gsa:
enabled: true
update_rate: 1
gst:
enabled: true
update_rate: 1
gsv:
enabled: true
update_rate: 1
main_talker_id: gn
rmc:
enabled: true
update_rate: 1
vtg:
enabled: true
update_rate: 1
zda:
enabled: true
update_rate: 1
serial:
ebp:
enabled: true
update_rate: 1
gga:
enabled: true
update_rate: 1
gsa:
enabled: true
update_rate: 1
gst:
enabled: true

update_rate: 1
gsv:
 enabled: true
 update_rate: 1
main_talker_id: gn
rmc:
 enabled: true
 update_rate: 1
vtg:
 enabled: true
 update_rate: 1
zda:
 enabled: true
 update_rate: 1
tcpcli:
 ebp:
 enabled: true
 update_rate: 1
 gga:
 enabled: true
 update_rate: 1
 gsa:
 enabled: true
 update_rate: 1
 gst:
 enabled: true
 update_rate: 1
 gsv:
 enabled: true
 update_rate: 1
 main_talker_id: gn
 rmc:
 enabled: true
 update_rate: 1
 vtg:
 enabled: true
 update_rate: 1
 zda:
 enabled: true
 update_rate: 1
tcpsvr:
 ebp:
 enabled: true
 update_rate: 1
 gga:
 enabled: true
 update_rate: 1
 gsa:
 enabled: true
 update_rate: 1

```
gst:
  enabled: true
  update_rate: 1
gsv:
  enabled: true
  update_rate: 1
main_talker_id: gn
rmc:
  enabled: true
  update_rate: 1
vtg:
  enabled: true
  update_rate: 1
zda:
  enabled: true
  update_rate: 1
settings:
  bluetooth:
    format: NMEA
  serial:
    baud_rate: 38400
    device: ttyEXTS0
    format: ERB
  tcpcli:
    address: localhost
    format: ERB
    port: 9000
  tcpsvr:
    format: LLH
    port: 9001
positioning_settings:
  elevation_mask_angle: 15
  glonass_ar_mode: false
gnss_settings:
  positioning_systems:
    beidou: false
    galileo: true
    glonass: true
    gps: true
    qzss: true
    sbas: true
  update_rate: 1
  gps_ar_mode: fix-and-hold
  max_horizontal_acceleration: 1
  max_vertical_acceleration: 1
  positioning_mode: kinematic
  snr_mask: 35
...

```

[/details]